


GOPO 7W SPOT EMP

Empotrable redondo con fuente de luz recedida y orientable. Regulacion 360°



potencia	ángulo	color (K)	flujo	eficiencia	dim	driver	código
7W	24°	2700K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1110.03
7W	24°	2700K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1110.06
7W	24°	3000K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1134.03
7W	24°	3000K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1134.06
7W	40°	2700K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1113.03
7W	40°	2700K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1113.06
7W	40°	3000K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1136.03
7W	40°	3000K	410lm	59 lm/W	TRIAC	EXTERNO	06-AA95.1136.06

INFORMACIÓN TÉCNICA

CRI	>90
INDICE DE PROTECCIÓN	20
RESISTENCIA AL IMPACTO MECÁNICO	
CLASE	II
TENSIÓN	25-42

INFORMACIÓN GENERAL

USO	
SUPERFICIE	Techo
ILUMINACIÓN	Directa
MEDIDAS	Ø120x58mm
CUT OUT	Ø110x55mm
PESO (KG)	0.42
REGULACIÓN	
COLOR	Blanco Texturado - Negro Texturado



bridge lux.



IP20

